


□□□□□□

SFENG 1984 精密探针 ( 4 探针 ) 探针

□□□□□





SF-P100-E

### 技术规格 PROBE SPECIFICATIONS

Recommended minimum center 最小间距	1.90mm(.0748 ")
Mounting hole size 钻孔尺寸	压克力: 1.35mm(.0532 ") 电木板、玻璃纤维板: 1.40mm(.0551 ")
Full travel 行程	6.3(.2481 ")
Spring force 弹簧压力	120g(克)
Materials and finishes 材料及涂饰	Plunger:SK4, Ni or Au plated BeCu, Ni or Au plated Phosphor bronze, Ni or Au plated Barrel:Phosphor bronze, Au plated Spring:Stainless steel
Current rating 额定电流	3A(安培)
Contact resistance 接触电阻	50mΩ(毫欧姆)

Receptacle specifications  
Materials and finishes: Phosphor bronze,Gold plated





## 技术规格 PROBE SPECIFICATIONS

Recommended minimum center 最小间距	2.54mm(.1000")
Mounting hole size 钻孔尺寸	压克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
Materials and finishes 材料及涂饰	Barrel: Brass, Gold plated
Connections 接线形式	Crimp: R100-VCR2.5, R100-CR Solder cup: R100-VSC2.5, R100-SC Wire wrap: R100-VW2.5, R100-WW, R100-WW(双环2.5), R100-WW(双环)

Receptacle specifications  
Materials and finishes: Phosphor bronze, Gold plated

□□□□□□□□:

□□□□	SF-P100
□□□□□□	1□90mm□.0748"□
□□□□□□	□□□□:1.35mm□.0532"□ □□□□□□□□□□□□□□□□:1.40mm□.0551"□
□□□□□□	6.30□.2481"□
□□□	120g
□□□□□□	□□□□□□□□Cu□Rh□□□□ □□□□□□□□□□□□ □□□□□□□□□□□□
□□□□□□	3A







1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection




5. Finished products



6. Packing



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope



Q1. 請說明...

A1: 請說明...

Q2. 請說明...

A2: 請說明 QC 請說明... 1 請說明...

Q3. 請說明...

A3: 請說明...

Q4. 請說明...

A4: 請說明...

Q5. 請說明...

A5: 請說明...

Q6. 請說明...

A6: 請說明...

Q7. OEM 與 ODM 的區別?

A7: 請說明 OEM / ODM 的區別 . P 請說明...

Q8. 請說明...

A8: T/T 請說明 L/C 請說明 MOQ 請說明

請說明

請說明 DHL UPS FedEx TNT EMS 請說明

請說明 Exwork FOB CNF CIF 請說明





2023 ISO Certificate



Patent for Coaxial Structure



Patent for Honeycomb current probe











□□□□□□





CIBF 2021

苏州胜亿福睿电子科技有限公司  
Suzhou Shengyifurui Electronic Technology Co., Ltd

No.3B013

