

□□□□

□	SFENG
Item□	SF-P100
□□	□□
□□□□	□□□□□7□□□□

SF-P100

Probe specifications SF-P100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Full travel(行程): 6.40(.2520")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰): Plunger: Be Cu, Rh plated; SK4, Rh plated Barrel: Brass, Gold plated Spring: Stainless steel
- Current ration(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

SF-R100

Probe specifications SF-R100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Materials and finishes(材料及涂饰): Barrel: Brass, Gold plated
- Connections(接线形式): Crimp: R100-VCR2.5, R100-CR Solder cup: R100-VSC2.5, R100-SC Wire wrap: R100-VW2.5, R100-WW, R100-WW(双环2.5), R100-WW(双环) Terminal: R100-VW2.5(T), R100-WW双环2.5(T), R100-WW双环5.0(T), R100-WW双环(T)

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

□□□□

SF-P100-J

SFENG
The China's The World's



WWW.SF-PROBE.COM

SF-P100-B

SFENG
The China's The World's



www.chinapogopinsupplier.com

□□□□

□□□□□□ □□24□□□□

2.□□ □□OEM□□□

□□□□□□ □□□□□□□□□□□□□□□□□□

□□□□□□ □□□□□□□□□□□□□□□□□□

□□□□

□□□□□□□□PCB□ICT□FCT□□□□;

