

3A SF-PPA5.8 * 36-J / M3

□□

□□ □□	3A SF-PPA5.8 * 36-J / M3
□□□□□□	□□□□□□□□□□; □□□□□□□□□□; □□□□□□□□;
□□	400□
□ □□	3-10 □
□□	DHL / TNT / UPS / FEDEX

EW/r-9EX8-SVd-JS

Materials (Plated) (材質與鍍層):

Barrel (針套) : Brass (黃銅) , Au on Ni Plated

Plunger (針軸) : Brass (黃銅) , Au on Ni Plated

Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):

Contact Resistance (接觸電阻) : 50mΩ

Full Stroke (滿沖程) : 10mm

Spring Force (額定彈力) : 400±10%gf@ load 10mm






				名稱		胜峰探针 说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。	
				SF-PA5.8X36-J/M3			
标记	页数	更改文件号	签字	日期	图样标记	质量比例	
设计			标准化		S A	4:1	
校对			审定				
审核			制图	徐松孟			
工艺			日期	2016.10.07	共 1 页	第 1 页	



SFENG 有限公司

本公司符合 ISO9001-2008 及 RoHs

有限公司

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

□□

