

0000

00	SFENG
0000	SF-P50 00
0	00000
000	0000007000

0000



### SF-P020

**Probe specifications SF-P020 PL020 (技术规格)**

- Recommended minimum center (最小间距): 1.0mm (.0394")
- Mounting hole size (钻孔尺寸): 0.75mm (.0295")
- Full travel (行程): 2.0(.0787")
- Spring force (弹簧压力): 80g (克)
- Materials and finishes (材料及涂饰): Plunger: SK4, Rh plated; Barrel: Phosphor bronze, Gold plated; Spring: Music wire, Gold plated
- Current rating (额定电流): 1A (安培)
- Contact resistance (接触电阻): 120mΩ (毫欧姆)

**Receptacle specifications**  
Materials and finishes: Phosphor bronze, Gold plated

SF-P020-B  
SF-PL020-B

### SF-P50

**Probe specifications SF-P50 (技术规格)**

- Recommended minimum center (最小间距): 1.27mm (.0500")
- Mounting hole size (钻孔尺寸): V: 0.90mm (.0354") W: 0.95mm (.0374")
- Full travel (行程): 2.5(.0984")
- Spring force (弹簧压力): 100g
- Materials and finishes (材料及涂饰): Plunger: Be Cu, Rh plated; SK4, Rh plated; Barrel: Phosphor bronze, Gold plated; Spring: Stainless steel
- Current rating (额定电流): 1.5A (安培)
- Contact resistance (接触电阻): 50mΩ (毫欧姆)

SF-P50-E

Noted: Specifications subject to change without notice! 规格变更不另行通知

□□□□□

1. □□□□□□ □24□□□□□□□□□□
2. □□ □□□□□□□□, OEM □□□□□□
3. □□□□□□ □□□□, □□□□□□□□□□□□□□□□□
4. □□□□□□ □□□□□□□□□□□□□□, □□□□□□

□□□□

□□ PCB □ICT □FCT □□□□□□□□ (□);

□□□ (□□□), □□□□□□□□□□□□□□□□, □□□□□□□□□□□□□□ & □□□□;

BGA □□□□□□□□□□□□;

□□□□□□, □□□, LM □, □ QZ □ VZ □□;

□□□□□□□□□□□□□□;

□□ & □□/□□;

□□□□□□□□, 30 # OK □, □□□, □□□, □□□□

□□□□

