

□□□□

□□□□	SF3081
□□□□□	5.0mm
□□□	8000□
□□ □□/□□	BeCu/Au
□□/□□1	□□□
□□	SUS304
□□/□□2	□□
□□□	150□□
□□	□□0.5mΩ
□□	ΔT□20°C
□□ □□	OEM & ODM
□□□□□	100PCS
□□	□□□□□□
□□	100% T/T □□□
□□□□	□□□□□ 5-10 □

□□ □□

SF-18.0*76.0

Materials(Plated) (材質與鍍層) :
 Barrel(針套) : POM(賽鋼) , /
 Plunger(電壓針軸) : BeCu(鈹銅) , Au on Ni Plated
 Plunger(電流針軸) : Cu(探針專用銅) , Au on Ni Plated
 Spring(彈弓) : Spring Wire(彈簧鋼線) , Ni Plate
 Insulator(絕緣體) : PEEK or PTFE , /

Specifications (技術要求) :
 Current Rating(額定電流) : ??A
 Contact Resistance(接觸電阻) : ??mΩ

	名稱	移動距離(mm)	%壓縮	全壓縮
彈力規格	電流針	12	11kgf	15.5kgf
	電壓針	3	-	1200gf

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



Measuring Equipment >



Measuring Equipment:

- 1. Agilent current testing;
- 2. Quadratic element measurement
- 3. Load Curve Meter
- 4. Bond Test
- 5. Life Fatigue Test



