

0000

0	SFENG
0000	0000SF-P125-H
00	00000
0000	00000070000

0000

胜峰探针

SFENG

The China's The World's














chinapogopinsupplier.com









Probe specifications SF-P125(技术规格)

- Recommended minimum center(最小间距): 3.17mm.(1248 ")
- Mounting hole size(钻孔尺寸):
 压入力: 2.40mm(.0945 ")
 电木板、玻璃纤维板: 2.45mm(.0965 ")
- Full travel(行程): 6.30(2480 ")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰):
 Plunger: Be Cu, Rh plated;
 Barrel: Brass, Gold plated
 Spring: Stainless steel
- Current rating(额定电流): 5A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)
- Connections(接线形式):
 Crimp: R125-VCR, R125-CR
 Solder cup: R125-VSC, R125-SC

-21-

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

SF-P156



Probe specifications SF-P156(技术规格)

- Recommended minimum center(最小间距):
4.75mm(.1870")
- Mounting hole size(钻孔尺寸):
 压入力: 2.75mm(.1083")
电木板、玻璃纤维板: 2.80mm(.1102")
- Full travel(行程): 6.30(.2480")
- Spring force(弹簧压力): 250g
- Materials and finishes(材料及涂饰):
Plunger: Be, Cu, Rh plated;
Barrel: Brass, Gold plated
Spring: Stainless steel
- Current rating(额定电流): 5A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)
- Connections(接线形式):
Crimp: R156~CR156~CR
Solder cup: R156~V5C, R156~SC

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

-22-



□□□□□□ □□24□□□□

2. 如何選擇OEM廠商

[illegible][illegible]

PCB ICT FCT

Pogo□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□;

□□□□□BGA□□□□□;

LMQZVZ;

&/;

30OKPOM

