

□□□□

□□	SFENG
□□□□	SF-P020-J
□□	□□□□□□□□□□
□	□□□□□□□□
□□□	SK4□□□□□
□□□	80□
□□□□	2.0□□
□□□□□	1A
□□□□	120MΩ
□□	1.0□□
□□□□□	0.75□□
□□□□□	100□
□□□□	□□□□□7□□□□□□

□□□□


胜峰探针
SFENG
The China's The World's

RoHS

QUALITY ASSURED FIRM
ISO 9001
SGS

CE

chinapogopinsupplier.com



Probe specifications SF-P020 PL020 (插)

- Recommended minimum center(最小间距): 1.0mm(.0394 ")
- Mounting hole size(钻孔尺寸): 0.75mm(.0295 ")
- Full travel(行程): 2.0(.0787 ")
- Spring force(弹簧压力): 80g(克)
- Materials and finishes(材料及涂饰):
 Plunger:SK4,Rh plated
 Barrel:Phosphor bronze,Gold plated
 Spring:Music wire,Gold plated
- Current ration(额定电流): 1A(安培)
- Contact resistance(接触电阻): 120mΩ(毫欧姆)

Receptacle specifications

Materials and finishes: Phosphor bronze, Gold plated

□□□□□

- 1.Reply□□□□withn 24□□□□□□
- 2.Customized□□□□□□□□OEM□□
- 3.Delivery□□□□□□□□□□□□□□□□
- 4.□□□□□□□□□□□□□□□□□□□□

□□□□

- PCB□ICT□FCT□□□;
- usuallytemporary□□
- ;

interconnectApplications;

--□□probef orBGA□□□□; semiconudtion□□;







--□□□□□□□□coatingpin□LM□withQZ□□□□; VZseries;

--□□□□□□□□□□□□□□□□...

--□□□□□□;□□/□□;

--□□□□□□□□□□□□30□OKwire□□□□□□POM□Ironhinge□

□□□□

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

□□□□

