


規格


品名	SFENG
型番	SF-P080
材質	銅
色	黒
寸法	15mm
重量	1.5mm0.0590"mm
電圧	0.3A
電流	260mW
電圧降	0.45mm0.0177"mm
電圧降	0.35mm0.0138"mm
MOQ	100 個
備考	100個7mmmm

規格


SF-P080




-J



SF-P080-B



SF-R080-VR



SF-R080-VRW

Probe specifications SF-P080(技术规格)

- Recommended minimum center(最小间距): 0.45mm(.0177 ")
- Mounting hole size(钻孔尺寸): 0.35mm(.0138 ")
- Full travel(行程): 1.5(.0590 ")
- Spring force(弹簧压力): 15g(克)
- Materials and finishes(材料及涂饰):
Plunger:SK4,Rh plated
Barrel:Phosphor bronze,Gold plated
Spring:Music wire,Gold plated
- Current ration(额定电流): 0.3A(安培)
- Contact resistance(接触电阻): 260mΩ(毫欧姆)

Receptacle specifications

Materials and finishes: Phosphor bronze, Gold plated



chinapogopinsupplier.com

□□□□BGA□□□□□□;

LMQZVZ;

;

30OKPOM

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

