



SFENG 1984 PCB



品名	SF-420*4850
规格	7.7mm
重量	730±10%gf@7.7mm
材料	SK4 2-3u" 2-3u" 2-3u" SUS304
电流	15A
电阻	50mΩ
长度	100mm
数量	7000



6.7x5.5φ 探针

Materials (Plated) (材質與鍍層):

① Barrel (針套)	: Brass (黃銅)	, Ni Plated
② Plunger (針軸)	: BeCu (鈹銅)	, Ni Plated
③ Tip (頭部)	: Brass (黃銅)	, Au on Ni Plated
Spring (彈弓)	: Spring Wire (彈簧鋼絲)	, Ni Plated

Specifications (技術要求):

Full Stroke (滿沖程)	: 9.0mm
Spring Force (額定彈力)	: 1000±10%gf@ load 9.0mm

				名稱		大電流φ5.5×49		勝峰探針	
設計	校對	審核	工藝	標準化	製圖	日期	圖樣標記	質量	比例
					徐松孟	2015.11.19	S A		4:1
				共 1 頁		第 1 頁		說明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: X. ±0.2 X.X ±0.1 X.XX ±0.05	



1. 24
2. OEM
- 3.
- 4.



1. PCB ICT FCT
2. Pogo pin
3. BGA
4. QZ VZ LM
- 5.
6. /
7. 30# OK POM





1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope



A5: [Placeholder]

Q6. [Placeholder]

A6: [Placeholder]

Q7. [Placeholder] **OEM** [Placeholder] **ODM** [Placeholder]

A7: [Placeholder] OEM/ODM [Placeholder]

Q8. [Placeholder]

A8: [Placeholder]