

□□ □□

□□	SF-PPA 5.5X24
□□	□□
□□	□□
□□	□□□
□□ □	300g±20%
□□□□□	500□
□□□□	7□

□□□□

田 Autodesk 教育版产品制作

NOTE

- Material
Plunger: Brass **C3604**
Barrel: Brass **C3604**
Spring: SUS304
Housing:
- Plating
Plunger: Au 2u" over 50~120u" Ni
Barrel: Au 2u" over 50~120u" Ni
Spring:
- Electrical
Rated current & voltage: DC 12V; 1.0A Max.
- Mechanical
Spring force: **300g±20%** at normal working height
Durability: 10,000 cycles(minimum)
- To ensure the best usage, please operate it based on the working height
Based on the engineering drawings, shall not exceed the maximum allowed compression
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- RoHS And REACH compliant product.

截面内部示意图

SF-PPA5.5X24				
第三角法	品名	PO80pin	日期	2022/04/26
未注公差参照标准	公差	材质	设计	ZFU XU
0 - ±0.1	0.02	客户料号	审核	
0.0 - ±0.05	0.03	表面处理	确认	
0.00 - ±0.02	0.02	镀金	单位	mm
0.000 = -	0.04	图号	比例	1:1 版本 REV:A
请勿实测图纸	0.02			

田 Autodesk 教育版产品制作

□□□□

