




SFENG 1984 [ICT](#)




00	SF-PH-18
0000000	4.30000.1693000
000000	3.50000.1378000
00000	13.0(5.118")
000	3000
0000	5A
00	5000
000	1000
0000	00000070000




SF-PH15-B3




SF-PH18-B3



SF-PH101-B3



SF-PM200-B3



技术规格 PROBE SPECIFICATIONS

	SF-PH15	SF-PH18	SF-PH101	SF-PM200
Recommended minimum center 最小间距	3.50mm(.1378 ")	4.30mm(.1693 ")	2.54mm(.1000 ")	2.54mm(.1000 ")
Mounting hole size 钻孔尺寸	3.00mm(.1181 ")	3.50mm(.1378 ")	2.00mm(.0787 ")	2.00mm(.0787 ")
Full travel 行程	13.0(.5118 ")	13.0(.5118 ")	15.0(.5905 ")	12.0(.4724 ")
Spring force 弹簧压力	300g	300g	300g	300g
Current ration 额定电流	5A(安培)	5A(安培)	5A(安培)	5A(安培)
Contact resistance 接触电阻	50m Ω (毫欧姆)	50m Ω (毫欧姆)	50m Ω (毫欧姆)	50m Ω (毫欧姆)



1. 24 个探针
2. OEM
3. 探针
4. 探针



1. 100% PCB ICT FCT
2. Pogo pin
3. BGA
4. QZ VZ LM
- 5.
6. /
7. 30# OK POM



1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection




5. Finished products



6. Packing





□□□□ DHL□UPS□FedEx□TNT□EMS □□□

Exwork FOB CNF CIF



Q1. 請說明

A1: 請說明

Q2. 請說明

A2: 請說明QC

Q3. 請說明

A3: 請說明

Q4. 請說明

A4: 請說明

Q5. 請說明

