

**Pogo Pin SF-PA5.8 by 36-J / M3**

□□

□□ □□	<b>□□Pogo Pin SF-PA5.8 by 36-J / M3</b>
□□□□□□	□□□□□□□□□□□□ □□□□□□□□□□□□ □□□□□□□□
□□	<b>400□</b>
□ □□	<b>3-10 □</b>
□□	<b>DHL / TNT / UPS / FEDEX</b>




EW/r-9EX8-SVd-JS

Materials (Plated) (材質與鍍層):  
 Barrel (針套) : Brass (黃銅) , Au on Ni Plated  
 Plunger (針軸) : Brass (黃銅) , Au on Ni Plated  
 Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):  
 Contact Resistance (接觸電阻) : 50mΩ  
 Full Stroke (滿沖程) : 10mm  
 Spring Force (額定彈力) : 400±10%gf@ load 10mm

				名稱	<b>胜峰探针</b> 说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。	
				SF-PA5.8X36-J/M3		
标记	页数	更改文件号	签字	日期		
设计			标准化		图样标记	质量比例
校对			审定		S A	4:1
审核			制图	徐松孟		
工艺			日期	2016.10.07	共 1 页	第 1 页



Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

□□

