




SFENG 1984 [redacted] [redacted]




品名	SF-PH-18
規格	4.30mm.1693mm
規格	3.50mm.1378mm
規格	13.0(5.118")
規格	300mm
規格	5A
規格	50mm
規格	100mm
規格	7mm




SF-PH15-B3




SF-PH18-B3



SF-PH101-B3



SF-PM200-B3



技术规格
PROBE SPECIFICATIONS

	SF-PH15	SF-PH18	SF-PH101	SF-PM200
Recommended minimum contact 最小间距	3.50mm(.1378")	4.30mm(.1693")	2.54mm(.1000")	2.54mm(.1000")
Mounting hole size 钻孔尺寸	3.00mm(.1181")	3.50mm(.1378")	2.00mm(.0787")	2.00mm(.0787")
Full travel 行程	13.0(.5118")	13.0(.5118")	15.0(.5905")	12.0(.4724")
Spring force 弹簧压力	300g	300g	300g	300g
Current rating 额定电流	5A(安培)	5A(安培)	5A(安培)	5A(安培)
Contact resistance 接触电阻	50mΩ(毫欧姆)	50mΩ(毫欧姆)	50mΩ(毫欧姆)	50mΩ(毫欧姆)



1. 24-pin probe
2. OEM
3. Probe specifications
4. Probe specifications



1. PCB ICT FCT
2. Pogo pin
3. BGA
4. QZ VZ LM
- 5.
- 6.
7. 30# OK POM



1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



A5: [Placeholder]

Q6. [Placeholder]

A6: [Placeholder]

Q7. [Placeholder] **OEM** [Placeholder] **ODM** [Placeholder]

A7: [Placeholder] OEM/ODM [Placeholder]

Q8. [Placeholder]

A8: [Placeholder]