



	SFENG
Item	SF-P100
	0000070000

SF-P100

SF-P100-E

Probe specifications SF-P100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670")
电木板、玻璃纤维板: 1.75mm(.0689")
- Full travel(行程): 6.40(.2520")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰):
Plunger: Be Cu, Rh plated; SK4, Rh plated
Barrel: Brass, Gold plated
Spring: Stainless steel
- Current rating(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

-A

-B

-J

-D

-E

-U3

-U

-V

-G

-H

-H2.0

-H2.5

H3.0

-LM

-T

-Q

-B3

-B7

SF-R100

SF-R100-SC

SF-R100-VCR2.5

SF-R100-CR

SF-R100-VW2.5(T)

SF-R100-WW双环2.5(T)

SF-R100-WW双环5.0(T)

SF-R100-WW双环(T)

SF-R100-VSC2.5

SF-R100-WW

SF-R100-WW(双环2.5)

SF-R100-WW(双环)

SF-R100-VW2.5

Probe specifications SF-R100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670")
电木板、玻璃纤维板: 1.75mm(.0689")
- Materials and finishes(材料及涂饰):
Barrel: Brass, Gold plated
- Connections(接线形式):
Crimp: R100-VCR2.5, R100-CR
Solder cup: R100-VSC2.5, R100-SC
Wire wrap: R100-VW2.5, R100-WW, R100-WW(双环2.5), R100-WW(双环)
Terminal: R100-VW2.5(T), R100-WW双环2.5(T), R100-WW双环5.0(T), R100-WW双环(T)

-19- Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

-20- Noted: Specifications subject to change without notice(注: 规格变动不另行通知)



SF-P100-D

SFENG
The China's The World's



www.chinapogopinsupplier.com

SF-P100-B

SFENG
The China's The World's



www.chinapogopinsupplier.com

□□□□

□□□□□□ □□□24□□□□

2.□□ □□□OEM□□□

□□□□□□ □□□□□□□□□□□□□□□□□□

□□□□□□ □□□□□□□□□□□□□□□□

□□□□

□□□□□□□□□□PCB□ICT□FCT□□□□;

Pogo test equipment & fixtures;



BGA test equipment;

LM, QZ, VZ test;

test equipment;

& test;

30 OK test equipment

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
