

Sonde de commutation micron pour le test de circuits imprimés

Spécification:

Brand	SFENG
Item number	SF-SW2.96*49MM
Plunger	Brass
Barrel	Brass
Spring	SUS
Spring Force	100g@1.5mm
MOQ	100 pcs
Lead time	Within 2 working days after receiving the payment
Payment	T/T, Western union, Paypal or others.

Image:



Dessin:



材质与电镀:

- 1. 塑料头: POM
- 2. 针杆: 黄铜镀金
- 3. 针套: 黄铜管镀金
- 4. 绝缘套: PEEK
- 5. 尾针: 磷铜管镀金

技术要求:

- 开关距离: 1.5mm
- 开关距离弹力: 100g±20g 1.5mm

Technical parameters:

- Working stroke: 1.5mm;
- Spring force: 100g±20g at 1.5mm.

Material and Plating:

- 1. Plastic tip: White POM;
- 2. Plunger: Brass, Au plating;
- 3. Barrel: Brass, Au plating;
- 4. Insulation sleeve: PEEK;
- 5. Tail pin: Phosphor bronze, Au plating;

		名称:		胜峰探针	
		新开关针 (改良)		说明:	
设计	标准化	图样标记	视图	质量	比例
校对	审定	S	A	1:1	1:1
审核	制图 HJQ	共 1 页 第 1 页		图纸编号:	
工艺	日期 2017-7-7				

Nos avantages:

- 1. we have 30 years experience in probe pin and have ourself factory.
- 2. we provide free sample and have a testing department.
- 3. we could manufacture products as your request.
- 4. we guarantee best price and good service.

Principale Produit:

Spring loaded pin (single) for PCB, ICT, FCT testing etc;
Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;
Double ended probe for BGA and Semiconductor testing;
Universal pin without spring, coating pin, LM pin with QZ and VZ series;
High current probe, Switch probe, Capacitance needle;
Terminal & receptacle /socket;
Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Équipement de test:

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

Paquet:

