

Production specifications

| | |
|--------------------|--------------------------------------|
| Item number | SF-P050-B |
| Pitch | 0.7mm |
| Mounting hole size | 0.50mm |
| Full travel | 2.0 |
| Spring force | 40g |
| Current ration | 0.5A |
| Current resistance | 50mΩ |
| MOQ | 100PCS |
| Payment | T/T |
| Delivery time | 5-10days after receiving the payment |

Product Pictures

SF-P060

Probe specifications SF-P060(技术规格)

- Recommended minimum center(最小间距): 0.65m(.0256")
- Mounting hole size(钻孔尺寸): 0.45mm(.0177")
- Full travel(行程): 1.5(.0590")
- Spring force(弹簧压力): 40g(克)
- Materials and finishes(材料及涂饰): Plunger:SK4,Rh plated; Barrel:Phosphor bronze,Gold plated; Spring:Music wire,Gold plated
- Current ration(额定电流): 0.5A(安培)
- Contact resistance(接触电阻): 200mΩ(毫欧姆)

Receptacle specifications
Materials and finishes: Phosphor bronze, Gold plated

SF-P060-B

SF-P050

Probe specifications SF-P050(技术规格)

- Recommended minimum center(最小间距): 0.70m(.0276")
- Mounting hole size(钻孔尺寸): 0.5mm(.0196")
- Full travel(行程): 2.0(.0787")
- Spring force(弹簧压力): 40g(克)
- Materials and finishes(材料及涂饰): Plunger:SK4,Rh plated; Barrel:Phosphor bronze,Gold plated; Spring:Music wire,Gold plated
- Current ration(额定电流): 0.5A(安培)
- Contact resistance(接触电阻): 180mΩ(毫欧姆)

Receptacle specifications
Materials and finishes: Phosphor bronze, Gold plated

SF-P050-B

-3-

Noted: Specifications subject to change without notice!注: 规格变动不另行通知

-4-



Production Flow



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing

Testing Equipment

Measuring Equipment >



Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test

Packing



Main products

- 1.Spring loaded pin(single)for PCB,ICT,FCTtesting etc;
- 2.Pogo pin(connector)to establish connection between two printed circuit boards for charging,locating,battery,semiconductor&interconnector applications;
- 3.Double ended probes for BGA and semiconductor testing;
- 4.Universal pin without spring,coating pin,LM pin with QZ and VZ series;
- 5.High current probe,switch probe,capacitance needle;
- 6.Terminal&receptacle/socket;
- 7.Other related electronic components,Jig locks,POM and etc.

Whatever you want,please contact us without hesitation ,and we will try our best to meet your requirement within our capability.

Our service

- 1.We can reply your inquiry within 24 working hours;
- 2.Customized design is availble and OEM are welcomed;
- 3.We can deliver the probe pins to our clients all over the world with speed and precision.

4. We can provide the lowest price with high quality products to our clients.