Spécifications de Produition

Numéro d'article	SF-P125-J
Pas	1,90 mm
Taille du trou de montage	Plaque de pression : 1,35 Panneau en fibre de verre : 1,40 mm
CNotrese complète	4,5 mm
Force du ressort	180 ± 20 % gf @ charge 4,5 mm
Ration actuelle	3A
Résistance actuelle	≤50mΩ
MOQ	100 pièces
Paiement	T/T
Délai de livraison	5 à 10 jours après réception du paiement

Product Des photos



SF-P125

SF-R125-VCR



SF-R125-VSC



SF-R125-CR



SF-R125-SC





SF-P125-E



Probe specifications SF-P125(技术规格)

- Recommended minimum center(最小间距):
  3.17mm(.1248 ")
- Mounting hole size(钻孔尺寸):
  压克力：2.40mm(.0945 ")
  电木板、玻璃纤维板：2.45mm(.0965 ")
- Full travel(行程)：6.30(.2480 ")
- Spring force(弹簧压力)：200g
- Materials and finishes(材料及涂饰):
  Plunger:Be Cu,Rh plated;
  Barrel:Brass,Gold plated
  Spring:Stainless steel
- Current ration(额定电流)：5A(安培)
- Contact resistance(接触电阻)：50mΩ(毫欧姆)
- Connectioins(接线形式):
  Crimp：R125-VCR,R125-CR
  Solder cup：R125-VSC，R125-SC

Noted：Specifications subject to change without notice(注：规格变动不另行通知)

SF-P156





SF-P156-E

SF-R156-VCR



SF-R156-VSC



SF-R156-CR



SF-R156-SC



Probe specifications SF-P156(技术规格)

- Recommended minimum center(最小间距):
  4.75mm(.1870 ")
- Mounting hole size(钻孔尺寸):
  压克力：2.75mm(.1083 ")
  电木板、玻璃纤维板：2.80mm(.1102 ")
- Full travel(行程)：6.30(.2480 ")
- Spring force(弹簧压力)：250g
- Materials and finishes(材料及涂饰):
  Plunger:Be Cu,Rh plated;
  Barrel:Brass,Gold plated
  Spring:Stainless steel
- Current ration(额定电流)：5A(安培)
- Contact resistance(接触电阻)：50mΩ(毫欧姆)
- Connectioins(接线形式):
  Crimp：R156-VCR,R156-CR
  Solder cup：R156-VSC，R156-SC

Noted：Specifications subject to change without notice(注：规格变动不另行通知)

SFENG
The China's The World's

Production Couler

Production Flow (生产流程)

SFENG
The China's The World's

1. raw material warehouse

2. Lathe workshop

3. Assemble workshop

4. Quality inspection

5. Finished products

6. Packing

Essai Équipement

Measuring Equipment

Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test

Emballage

Principal des produits

1. Broche à ressort (simple) pour les tests PCB, TIC, FCT, etc.
2. Broche Pogo (connecteur) pour établir une connexion entre deux cartes de circuits imprimés pour les applications de chargement, de localisation, de batterie, de semi-conducteur et d'interconnecteur ;
3. Sondes à double extrémité pour les tests BGA et semi-conducteurs ;
4. Broche universelle sans ressort, broche de revêtement, broche LM avec séries QZ et VZ ;
5. Sonde à courant élevé, sonde de commutation, aiguille de capacité ;
6.Terminal&prise/prise ;
7.Autres composants électroniques liés, verrous gabarits, POM et etc.

Quoi que vous souhaitiez, veuillez nous contacter sans hésitation et nous ferons de notre mieux pour répondre à vos besoins dans la limite de nos capacités.

Our service

1.Nous pouvons répondre à votre demande dans 24 heures ouvrées ;
2. Une conception personnalisée est disponible et les OEM sont les bienvenus ;
3. Nous pouvons livrer les broches de la sonde à nos clients partout dans le monde avec rapidité et précision.
4. Nous pouvons fournir à nos clients le prix le plus bas avec des produits de haute qualité.