

Product Specification

Brand	SFENG
Item number	Guide pin
Material	Iron
Lead time	7 working days after receiving the payment

Product Picture





Our Service (A rial, 00 000 000 00)

1. We can reply your inquiry within 24 working hours.
2. Customized design is available and OEM are welcomed.
3. We can deliver the probe pins to our clients all over the world with speed and precision.
4. We can provide the lowest price with high quality product to our client .

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;







Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control

Spring exhausted tester	DC power supply	Current resistance tester
 A tall, white, industrial-grade cabinet with a glass door and a control panel on the right side.	 A white, rectangular device with a black front panel. It features a red emergency stop button, a red power switch, and several output terminals with colored caps (red, black, blue, red).	 A white, rectangular device with a large green digital display showing '8888'. It has a warning symbol and a dial on the right side.
Microscope	Tensile strength tester	Spring tester
 A white and black compound microscope with a large objective lens and a stage.	 A blue and white machine with a vertical column and a horizontal arm, used for testing the tensile strength of materials.	 A white and blue machine with a vertical column and a horizontal arm, used for testing the spring properties of materials.

Packing Picture

