

Product information

| | |
|--------------|-----------------|
| Item | SF-PPA 5.5X24 |
| Plunger | brass |
| Body | brass |
| Spring | Stainless steel |
| Spring force | 300g±20% |
| MOQ | 500pcs |
| Lead time | 7 days |

Product drawing

由 Autodesk 教育版产品制作

NOTE

- Material
Plunger: Brass C3604
Barrel: Brass C3604
Spring: SUS304
Housing:
- Plating
Plunger: Au 2u" over 50~120u" Ni
Barrel: Au 2u" over 50~120u" Ni
Spring:
- Electrical
Rated current & voltage: DC 12V; 1.0A Max.
- Mechanical
Spring force: **300g±20%** at normal working height
Durability: 10,000 cycles(minimum)
- To ensure the best usage, please operate it based on the working height
Based on the engineering drawings, shall not exceed the maximum allowed compression
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- RoHS And REACH compliant product.

针头
针管
弹簧
后塞车件

截面内部示意图

SF-PPA5.5X24

| | | | | | |
|--------------|--------|------|---------|----|--------------|
| 第三角法 | | 品名 | posopia | 日期 | 2022/04/26 |
| 未注公差参照标准 | 0.02 | 规格 | | 设计 | ZFU XU |
| 0 - ±0.1 | ◎ 0.03 | 材质 | | 审核 | |
| 0.0 - ±0.05 | ⊥ 0.02 | 客户料号 | | 确认 | |
| 0.00 - ±0.02 | ∠ 0.04 | 表面处理 | 镀金 | 单位 | mm |
| 0.000 - - | ∠ 0.02 | 图号 | | 比例 | 1:1 版本 REV:A |
| 请见实物图纸 | | | | | |

由 Autodesk 教育版产品制作

Factory

