

Product Picture



D007-1201-1524-0EZH-55ZJ4

Materials (Plated) (材質與鍍層):

①Plunger (針軸)	: BeCu (鍍銅)	, Au on Ni Plated
②Barrel (針套)	: Brass (黃銅)	, Au on Ni Plated
③Insulation sleeve (絕緣套)	: Peek (聚醚醚酮)	, /
④Solder Connection (焊接杆)	: BeCu (鍍銅)	, Au on Ni Plated
⑤Receptacle (插座)	: Brass (黃銅)	, Au on Ni Plated
⑥Spring (彈弓)	: SUS304 (不鏽鋼線)	, /

Specifications (技術要求):

Current Rating (額定電流)	: 3A
Contact Resistance (接觸電阻)	: <50mΩ
Full Stroke (滿行程)	: 5.2mm
Switching Path (開關行程)	: 1.7mm
①Spring Force (額定彈力)	: 100~150gf@ Load 5.0mm
②Spring Force (額定彈力)	: 200~250gf@ Load 3.3mm
The total set elastic (總組彈性)	: 350~400gf@ Load 5.0mm

				名稱		开关针		胜峰探针	
				SF265-H230-425L-102L-400G					
标记	次数	更改文件号	签字	日期	图样标记		质量比例		
设计					S A		4:1		
校对									
审核									
日期	12016.03.24		徐松孟						
				共	1	页	第	1	页

说明: 1、所有尺寸的单位为mm
2、未注图示尺寸公差: 按GB1804-79 10级精度执行。

Our Service

1. We can reply your inquiry within 24 working hours.
2. Customized design is available and OEM are welcomed.
3. We can deliver the probe pins to our clients all over the world with speed and precision.
4. We can provide the lowest price with high quality product to our client .

Main Products

- Spring loaded pin (single) for PCB, ICT, FCT testing etc;
- Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;
- Double ended probe for BGA and Semiconductor testing;
- Universal pin without spring, coating pin, LM pin with QZ and VZ series;
- High current probe, Switch probe, Capacitance needle;
- Terminal & receptacle /socket;
- Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control



Packing Picture

