

## Product Picture



### SF-GP Series Item



Item	Specification & Size				Drilling hole size
GP2.4	Barrel (A)	φ 2.4mm	Plunger (D)	φ 1.75mm	φ 2.40mm
GP3.2	Barrel (A)	φ 3.2mm	Plunger (D)	φ 2.50mm	φ 3.20mm
GP4.0	Barrel (A)	φ 4.0mm	Plunger (D)	φ 3.50mm	φ 4.00mm
GP5.0	Barrel (A)	φ 5.0mm	Plunger (D)	φ 4.00mm, φ 6.00mm	φ 5.00mm
GP5.2	Barrel (A)	φ 5.2mm	Plunger (D)	φ 4.00mm, φ 6.00mm	φ 5.20mm
GP6.0	Barrel (A)	φ 6.0mm	Plunger (D)	φ 5.00mm	φ 6.00mm

## Our Service

1. We can reply your inquiry within 24 working hours.
2. Customized design is available and OEM are welcomed.
3. We can deliver the probe pins to our clients all over the world with speed and precision.
4. We can provide the lowest price with high quality product to our client .

## Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

## Quality Control



## Packing Picture

