

**Surgical Pogo Pin SF-PA5.8 by 36-J/M3**

# Specification

<b>Item Name</b>	<b>Surgical Pogo Pin SF-PA5.8 by 36-J/M3</b>
<b>Material and finishes</b>	<b>Plunger:Brass,gold plated over nickel plated; Barrel:Brass,Gold plated over Nickel plated; Spring:Stainless steel;</b>
<b>Spring force</b>	<b>400g</b>
<b>Lead time</b>	<b>3-10 days</b>
<b>Shipment</b>	<b>DHL/TNT/UPS/FEDEX</b>

EW/r-9EX8-SVd-JS

**Materials(Plated) (材質與鍍層):**  
 Barrel(針套) : Brass(黃銅) , Au on Ni Plated  
 Plunger(針軸) : Brass(黃銅) , Au on Ni Plated  
 Spring(彈弓) : SUS304(不鏽鋼) , /

**Specifications (技術要求):**  
 Contact Resistance(接觸電阻) : 50mΩ  
 Full Stroke(滿行程) : 10mm  
 Spring Force(額定彈力) : 400±10%gf@ load 10mm

				名稱		胜峰探针	
				SF-PA5.8X36-J/M3		说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。	
标记	页数	更改文件号	签字	日期	图样标记	质量比例	
设计			标准化		S A	4:1	
校对			审定				
审核			制图	徐松孟			
工艺			日期	2016.10.07	共 1 页	第 1 页	



## **SFENG Probe factory introduction**

Suzhou Shengyifurui Electronic Technology Co.,Ltd is specializing in the spring probe&the pogo pin with high quality,low price and fast delivery.We have our own brand,we always devote ourselves to achieving international standards,our company have passed the ISO9001-2008 quality managements certification and our products are qualified of RoHs.

## **Quality Test equipment**

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

## Packaging

