

## Specifications

Brand	SFENG
Model	Screw probe SFM137
Plunger	Beryllium copperBeryllium copper
Body	Brass
Spring	stainless steel
Spring force	Customized
Full travel	
Rated voltage	NO
Current Resistance	NO
Spacing	NO
Mounting dimensions	NO
MOQ	100
delivery time	7 Days after confirming order

## Product Image



**SFENG**  
The China's The World's



*Screw test probe drawing*

# SF-M137




可选用的针头形式				
材料	针头类型	针头 电镀	特殊版本	
			Φ	Φ (inch)
AU	TJ 	A		


类型	头部直径 A	台阶直径 B	头部长度 C	总长 D	安装高度 E
TJ01	0.65	1.50	4.00	29.90	14.80
TJ02	0.65	1.50	2.80	28.70	13.60
TJ03	0.65	1.50	3.30	29.20	14.10
TJ04	0.65	1.50	3.40	29.30	14.20
TJ05	0.70	1.50	4.00	29.90	14.80
TJ06	0.65	1.40	5.50	31.40	16.30
TJ07	0.65	1.50	1.50	27.40	12.30
TJ08	0.65	1.50	2.00	27.90	12.80
TJ09	0.65	1.50	2.50	28.40	13.30
TJ10	0.65	1.50	3.00	28.90	13.80
TJ11	0.65	1.50	3.50	29.40	14.30
TJ12	0.65	1.50	4.50	30.40	15.30
TJ13	0.65	1.50	5.00	30.90	15.80

## 安装和功能的尺寸

M137



MR137L



MR137L-V



用来测试电缆束的探针  
螺钉 螺丝 螺纹设计  
可用的螺旋工具

### 技术参数

间距: 2.54 mm/100mil  
 全行程: 4.40 mm  
 工作行程: 3.50 mm  
 预装弹力: 0.25/0.40/0.40/0.30/0.70/0.60 N  
 在工作行程下的弹力: 0.70/1.00/1.50/1.70/2.50/3.00 N

### 电气数据

电流: 3.0 A  
 电阻: ≤20 mOhm

### 材质

针管: 黄铜, 镀金  
 弹簧: 不锈钢  
 针杆: 铍铜, 镀金  
 套管: 黄铜, 镀金

### 推荐的钻孔直径

HP2361.1 (保温 隔热材料) 1.68...1.70 mm  
 HGW2372 (玻璃棉, 玻纤棉) 1.68...1.70 mm

## our service

1. Quick response.

- 2. Customized is accepted.
- 3. Short production time and fast delivery.
- 4. High quality and good price.

## **Main products**

Spring-loaded pin (single) of PCB, ICT, FCT testing;

Spring pin (connector) to establish a connection between two printed circuit boards for charging, positioning, batteries, semiconductors and amplifiers; interconnect applications;

BGA and semiconductor test double-ended probe;

Universal pin no spring, paint needle, LM pin QZ and VZ series;

High current probe, the probe switches, capacitors needle;

Pier and amplifier; socket / socket;

Other related electronic components, 30 # OK line, jig lock, POM, iron hinges, etc.

## **Production process**



**1. Raw material warehouse**



**2. Lathe workshop**



**3. Assemble workshop**



**4. Quality inspection**




**5. Finished products**




**6. Packing**


## **Testing equipment**



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope

## Packing & delivery

Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.

