

0000

|         |              |
|---------|--------------|
| 0000    | SFENG        |
| ITERM00 | SF-P100      |
| 000     | 0000         |
| 000000  | 000000007000 |

SF-P100

**Probe specifications SF-P100(技术规格)**

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Full travel(行程): 6.40(.2520")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰): Plunger: Be Cu, Rh plated; SK4, Rh plated Barrel: Brass, Gold plated Spring: Stainless steel
- Current rating(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

SF-R100

**Probe specifications SF-R100(技术规格)**

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Materials and finishes(材料及涂饰): Barrel: Brass, Gold plated
- Connections(接线形式): Crimp: R100-VCR2.5, R100-CR Solder cup: R100-VSC2.5, R100-SC Wire wrap: R100-VW2.5, R100-WW, R100-WW(双环2.5), R100-WW(双环) Terminal: R100-VW2.5(T), R100-WW双环2.5(T), R100-WW双环5.0(T), R100-WW双环(T)

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

0000

SF-P100-J

**SFENG**  
The China's The World's



[WWW.SF-PROBE.COM](http://WWW.SF-PROBE.COM)

SF-P100-B

**SFENG**  
The China's The World's



[www.chinapogopinsupplier.com](http://www.chinapogopinsupplier.com)

## 服務項目

1. 承接各種規格之鋼筆、鋼珠筆、24K金鋼筆、鋼珠筆
2. 承接各種規格之鋼筆、鋼珠筆、OEM、ODM、貼牌、代客設計
3. 承接各種規格之鋼筆、鋼珠筆、鋼筆、鋼珠筆、鋼筆、鋼珠筆
4. 承接各種規格之鋼筆、鋼珠筆、鋼筆、鋼珠筆、鋼筆、鋼珠筆

## 產品

PCB、ICT、FCT、各種規格之鋼筆、鋼珠筆、鋼筆、鋼珠筆



□□□□□□

