

□□□□

□□□□	SF1195
□□□	6.0mm
□□	△□□□20°C
□□□	550g
□□	30□□□□
□□	□10mΩ
MOQ	100□
□□□	T/T
□□	□□□□□□□□□□ 5 □ 10 □

□□ □□□□□

P1195-5.7-24.5

Materials (Plated) (材質與鍍層):

- ① Barrel (針套) : Brass (黃銅) , Au on Ni Plated
- ② Plunger (針軸) : Brass (黃銅) , Au on Ni Plated
- ③ Plunger (針軸) : BeCu (鉍銅) , Au on Ni Plated
- ④ Spring (彈弓) : SUS304 (不鏽鋼線) , /

Specifications (技術要求):

- Current Rating (額定電流) : 30A
- Contact Resistance (接觸電阻) : < 50mΩ

彈力規格	名稱	移動距離 (mm)	%壓縮 (g)	全壓縮 (g)
1	電流針②	8	550	800
	電壓針③	2	-	250
2	電流針	/	/	/
	電壓針	/	/	/

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection




5. Finished products



6. Packing



Measuring Equipment >



Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test



