

3A SF-PPA5.8 * 36-J / M3

□□

| | |
|--------|--|
| □□ □ | 3A SF-PPA5.8 * 36-J / M3 |
| □□□□□□ | □□□□□□□□□□□□□□□□□□□□□□; □□□□□□□□□□□□□□□□□□□□□□; □□□□□□□□□□□□□□□□□□□□□□ |
| □□□ | 400g |
| □ □□ | 3-10 □□ |
| □□ | DHL / TNT / UPS / □□□□□□ |

EW/r-9EX8-SVd-JS

Materials (Plated) (材質與鍍層):

- Barrel (針套) : Brass (黃銅) , Au on Ni Plated
- Plunger (針軸) : Brass (黃銅) , Au on Ni Plated
- Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):

- Contact Resistance (接觸電阻) : 50mΩ
- Full Stroke (滿行程) : 10mm
- Spring Force (額定彈力) : 400±10%gf @ load 10mm

| | | | | | | |
|------------------------|----|-------|-----|------------|--|-------|
| 名稱 SF-PA5.8X36-J/M3 | | | | | 胜峰探针 | |
| | | | | | 说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。 | |
| 标记 | 页数 | 更改文件号 | 签字 | 日期 | 图样标记 | 质量比例 |
| 设计 | | | 标准化 | | S A | 4:1 |
| 校对 | | | 审定 | | | |
| 审核 | | | 制图 | 徐松孟 | | |
| 工艺 | | | 日期 | 2016.10.07 | 共 1 页 | 第 1 页 |



SFENG 有限公司 鑽頭

Shengyifurui 有限公司 & 有限公司 ISO9001 - 2008 RoHs

有限公司

| | | |
|---|---|--|
| Spring exhausted tester | DC power supply | Current resistance tester |
|  |  |  |
| Microscope | Tensile strength tester | Spring tester |



□□□□□□

