

PCB / ICT 50

BeCu
;
;

- pls





- Recommended minimum center(最小间距):
1.0mm(.0394")
- Mounting hole size(钻孔尺寸): 0.75mm(.0295")
- Full travel(行程): 2.0(.0787")
- Spring force(弹簧压力): 80g(克)
- Materials and finishes(材料及涂饰):
Plunger:SK4,Rh plated
Barrel:Phosphor bronze,Gold plated
Spring:Music wire,Gold plated
- Current rating(额定电流): 1A(安培)
- Contact resistance(接触电阻): 120mΩ(毫欧姆)


Receptacle specifications
Materials and finishes: Phosphor bronze,
Gold plated

Noted: Specifications subject to change without notice/注：规格变动不另行通知

—8—



- Recommended minimum center(最小间距):
1.27mm(.0500")
- Mounting hole size(钻孔尺寸):
V: 0.90mm(.0354")
W: 0.95mm(.0374")
- Full travel(行程): 2.5(.0984")
- Spring force(弹簧压力): 100g
- Materials and finishes(材料及涂饰):
Plunger: Be Cu, Rh plated; SK4, Rh plated
Barrel: Phosphor bronze, Gold plated
Spring: Stainless steel
- Current rating(额定电流): 1.5A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧)



Noted: Specifications subject to change without notice(注: 规格变动不易行通知)



30

[illegible]

3.

4.



Spring loaded pin (single) for PCB, ICT, FCT testing etc;
Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;
Double ended probe for BGA and Semiconductor testing;
Universal pin without spring, coating pin, LM pin with QZ and VZ series;
High current probe, Switch probe, Capacitance needle;
Terminal & receptacle /socket;
Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc



Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		



