



□□□□	SFENG
ITERM□□	SF-P11
□□□	□□□□
□□□□□□	□□□□□□□□7□□□

### SF-P11

SP-P11-E

**Probe specifications SF-P11(技术规格)**

- Recommended minimum center(最小间距): 1.90mm(.0748")
- Mounting hole size(钻孔尺寸): 压克力: 1.35mm(.0532")  
电木板、玻璃纤维板: 1.40mm(.0551")
- Full travel(行程): 4.0(.1575")
- Spring force(弹簧压力): 150g
- Materials and finishes(材料及涂饰):  
Plunger: Be Cu, Rh plated  
Barrel: Brass, Gold plated  
Spring: Stainless steel
- Current ration(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

### SF-R11

**Probe specifications SF-R11(技术规格)**

- Recommended minimum center(最小间距): 1.90mm(.0748")
- Mounting hole size(钻孔尺寸): 压克力: 1.35mm(.0532")  
电木板、玻璃纤维板: 1.40mm(.0551")
- Materials and finishes(材料及涂饰): Barrel: Brass, Gold plated
- Connections(接线形式):  
Crimp: R11-VCR, R11-CR, R11-CR4.0  
Solder cup: R11-VSC, R11-SC, R11-SC4.0  
Wire wrap: R11-VW, R11-VW4.0

-15-

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

-16-



SF-P11-J

**SFENG**  
The China's The World's



[WWW.SF-PROBE.COM](http://WWW.SF-PROBE.COM)

SF-P11-B

# SFENG

The China's The World's



[www.chinapogopinsupplier.com](http://www.chinapogopinsupplier.com)

## 服務宗旨

1. 竭誠為廣大客戶提供優質、快捷、專業的服務
2. 竭誠為廣大客戶提供優質、快捷、專業的服務
3. 竭誠為廣大客戶提供優質、快捷、專業的服務
4. 竭誠為廣大客戶提供優質、快捷、專業的服務

## 服務項目

PCB、ICT、FCT、組裝、測試、維修、保養、維修、保養、維修、保養



□□□□□□

