□□□□

□□□□	SFENG
□□□□	SF P058 B
□□□	Ni □□□□□□□□
□□□ □□□	□□□□□□□□□ 7 □□□

□□□□□



針軸 Plunger
高碳鋼鍍金
SK4 with Gold Plated
內管 Barrel
磷青銅鍍金
Phospher Bronze with Gold Plated
彈簧 Spring
琴鋼線鍍金
Music Wire with Gold Plated
外管 Receptacle
磷青銅鍍金
Phosphor Bronze with Gold Plated
最小中心距 Min. Pitch
1.0mm [0.0394]
彈力最大行程
Spring Force @ Full Stroke
60g[2.12 oz]±20% @ 2.0mm[0.079]
2/3彈力行程
Spring Force @ 2/3 Stroke
45g[1.59 oz]±20%
額定電流 Current Rating
1A Continuous
接觸阻值 Contact Resistance
150 mΩ

□□□□□□□

2. □□□□□□ □□□□□□OEM □□□□□□□□□

3. □□ □□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□

4. □□ □□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□

□□□□□□□□□□□□□ICT□(□□□□) □ FCT □□□□□

□□□□ (□□□□) □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ 2 □□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□ BGA □□□□□□□□;

□□□□□□□□ □□□QZ□VZ □□□□; LM □□□□□□□□□□□□

□□□□□□□□□□□□□ □□□□□□□□;

□□□□□ □ □□□□□□/socket;

□□□□□□□□□□□30 # [ok] □□□□□□□□□□□□POM□□□□□□

□□□□□□□□

Spring exhausted tester	DC power supply	Current resistance tester
Microscope	Tensile strength tester	Spring tester

□□□□