

□□□□

□□□□	SF5150
□□□ □□□	3A
□□□□	50mΩ
□□□□□□	5.7mm
□□□□□□□□	4.0mm
□□□	150±20%gf@ □□ 4.0mm
MOQ	100□
□□□	T/T
□□	□□□□□□□□□□□□ 5 □ 10 □

□□ □□□□□□

Materials(Plated) (材質與鍍層) :
 Barrel(針套) : Brass(黃銅) , Au on Ni Plated
 Plunger(針軸) : Fe(易車鐵) , Ni Plated
 Spring(彈弓) : SUS (不銹鋼線) , /

Specifications (技術要求) :
 Current Rating(額定電流) : 3A
 Contact Resistance(接觸電阻) : ≤50mΩ
 Full Stroke(滿沖程) : 5.7mm
 Rated Stroke(額定沖程) : 4.0mm
 Spring Force(額定彈力) : 150±20%gf@ load 4.0mm

				名称:		胜峰科技	
				SF-P125-G1.02X2.2(L33.7)-HAT-61		说明:	
标记	处数	更改文件号	签字	日期	图样标记	视图	质量
设计					S	A	比例
校对					⊕		/
审核			HJQ		图纸编号:		
工艺			日期	2019-7-20	共 1 页	第 1 页	

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



Measuring Equipment >



Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test



