

□□□□

□□□□	SF-PPA 5.5X24
□□□□□□	□□
□	□□
□	□□□□□□
□□□	300g±20%
MOQ	500□
□□□□□□	7□

□□□□□

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

NOTE

- Material
Plunger: Brass C3604
Barrel: Brass C3604
Spring: SUS304
Housing:
- Plating
Plunger: Au 2u" over 50~120u" Ni
Barrel: Au 2u" over 50~120u" Ni
Spring:
- Electrical
Rated current & voltage: DC 12V; 1.0A Max.
- Mechanical
Spring force: 300g±20% at normal working height
Durability: 10,000 cycles(minimum)
- To ensure the best usage, please operate it based on the working height
Based on the engineering drawings, shall not exceed the maximum allowed compression
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- RoHS And REACH compliant product.

由 Autodesk 教育版产品制作

截面内部示意图

SF-PPA5.5X24

第三角法		品名	PO80pin	日期	2022/04/26
未注公差参照标准	○ 0.02	规格		设计	ZFU XU
0 - ±0.1	◎ #0.03	材质		审核	
0.0 - ±0.05	⊥ 0.02	客户料号		确认	
0.00 = ±0.02	▱ 0.04	表面处理	镀金	单位	mm
0.000 = -	∠ 0.02	图号		比例	1:1 版本 REV:A
请见实物图纸					

□□

