



SFENG 1984 (PCB))



Model	SF265-F500-425L-102L-400G
Thickness	5.20mm
Material	BeCuAuNi Au BeCuNi Au
Plating	SWP Au Ni
Current	3A
Resistance	50mΩ
Width	5.2mm
Height	1.7mm
Weight	70gf @ 1.70mm
Force	230gf @ 4/5
MOQ	100
Lead time	7



SF265-F300-425L-102L-400G

A
3.0
5.0

Materials (Plated) (材質與鍍層):

①Plunger (針軸)	: BeCu (鉍銅)	, Au on Ni Plated
②Barrel (針套)	: Brass (黃銅)	, Au on Ni Plated
③Insulation sleeve (絕緣套)	: Peek (聚醚醚酮)	, /
④Solder Connection (焊接杆)	: BeCu (鉍銅)	, Au on Ni Plated
⑤Receptacle (插座)	: Brass (黃銅)	, Au on Ni Plated
Spring (彈弓)	: SWP (琴鋼線)	, Au on Ni Plated

Specifications (技術要求):

Current Rating (額定電流)	: 3A
Contact Resistance (接觸電阻)	: < 50mΩ
Full Stroke (滿沖程)	: 5.2mm
Switching Path (開關行程)	: 1.7mm
Spring Force (額定彈力)	: 70gf@ load 1.7mm
Spring Force (額定彈力)	: 230gf@ load 1/4行程

				名稱	开关针		胜峰探针		
					SF265-F300-425L-102L-400G				
标记	处数	更改文件号	签字	日期	图样标记			质量比例	
设计			标准化						
校对			审定						
审核			制图	徐松孟					
工艺			日期	2016.03.30					
				共	1	页	第	1	页



1. 24
2. OEM
- 3.
- 4.



1. PCB ICT FCT
2. 2
3. BGA
4. QZ VZ LM
- 5.

