



SFENG 1984 (PCB) 8.0mm 5.0mm 1500±20%gf@5.0mm Cu Ni Ni SU304 20A ≤0.5mΩ 100 7



品名	SF-PH800*4850
规格	8.0mm
长度	5.0mm
重量	1500±20%gf@5.0mm
材料	Cu Ni Ni SU304
额定电流	20A
接触电阻	≤0.5mΩ
MOQ	100
备注	7



8.0

Materials (Plated) (材質與鍍層) :

Barrel (針套) : Brass (黃銅) , Ni Plated

Plunger (針軸) : BeCu (鈹銅) , Au on Ni Plated

Spring (彈弓) : SUS304 (不銹鋼線) , /

Specifications (技術要求) :

Current Rating (額定電流) : 20A

Contact Resistance (接觸電阻) : ≤0.5mΩ

Full Stroke (滿沖程) : 8.0mm

Rated Stroke (額定沖程) : 5.0mm

Spring Force (額定彈力) : 1500±20%gf@ load 5.0mm

					名称:		胜峰科技	
					SF-PH800X4850-H8.0(M)			
设计	处数	更改文件号	签字	日期	图样标记	视图	质量	比例
校对			审核		S	A	⊕	/
审核			制图	HJQ	图纸编号:			
工艺			日期	2022-5-20	共 1 页	第 1 页		



1. 24
2. OEM
- 3.
- 4.



1. PCB ICT FCT;
2. 2 ()
3. BGA
4. QZ VZ LM;
- 5.;
6. /;
7. 30# OK POM





1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope



A5: 100% payment in advance

Q6. Minimum order quantity

A6: 1000 pieces

Q7. OEM and ODM services available?

A7: Yes, OEM/ODM services are available. We can customize products according to your requirements.

Q8. Payment terms?

A8: T/T, L/C, MOQ, L/C