

□□□□

□□□□	SF3763
□□□	□□4.0×42.0mm
□□	□□□□□□:□□□□□□□□□□ □□□:□□□□□□□□□□□□ □□□□□: SUS
□□□□□□	10.0mm
□□□□□□□□	6.5mm
□□□	200±35gf□□□ 6.5mm
MOQ	100□
□□□	T/T
□□	□□□□□□□□□□ 5 □ 15 □

□□ □□□□□□

Materials(Plated) (材質與鍍層):
 Barrel(針套) : Brass(黃銅) , Ni Plated
 Plunger(針軸) : Brass(黃銅) , Ni Plated
 Spring(彈弓) : SUS (不銹鋼線) , /

Specifications (技術要求):
 Full Stroke(滿沖程) : 10.0mm
 Rated Stroke(額定沖程) : 6.50mm
 Spring Force(額定彈力) : 200±35gf@ load 6.50mm

					名称:		胜峰探针	
					SF-GP3. 5X42-B(R0. 25)		说明:	
					图样标记		1. 所有尺寸单位为mm	
					S A		2. 未注图示尺寸公差:按GB1804-79 11级精度执行	
					视图		图纸编号:	
					质量			
					比例		1:1	
					共 1 页		第 1 页	

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



Measuring Equipment >



Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test



