

36-J / M3 SF-PA5.8



□□ □□	<b>36-J / M3 SF-PA5.8</b>
□□□□□□	□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□; □□□□□□□□;
□□□	<b>400g</b>
□ □□	<b>3-10 □□</b>
□□	<b>DHL / TNT / UPS / FEDEX</b>

EW/r-9EX8-57d-JS

Materials (Plated) (材質與鍍層):

- Barrel (針套) : Brass (黃銅) , Au on Ni Plated
- Plunger (針軸) : Brass (黃銅) , Au on Ni Plated
- Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):

- Contact Resistance (接觸電阻) : 50mΩ
- Full Stroke (滿沖程) : 10mm
- Spring Force (額定彈力) : 400±10% load 10mm

		名稱	
		SF-PA5.8X36-J/M3	勝峰探針
标记	数量	更改文件号	签字 日期
设计		标准化	
校对		审定	
审核		制图	徐松孟
工艺		日期	2016.10.07
		图样标记	质量比例
		SA	4:1
		共 1 页	第 1 页






说明: 1、所有尺寸的单位为mm  
2、未注图示尺寸公差: 按GB1804-79 11级精度执行。



**SFENG** 有限公司

Shengyiifurui Electronic Technology Co., Ltd. 专业生产各种精密五金零件及电子元器件  
产品符合RoHS环保标准

000000

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

□□□□□□

