

11

SF-PA5.8X36-J/J-SF

Technical drawing of a probe pin (SF-PA5.8X36-J/J-SF) showing dimensions and materials. The drawing includes a cross-section view of the pin with the following dimensions and specifications:

- Thread: M3*0.5
- Barrel diameter: $\phi 4.60^{+0.01}_{-0.03}$
- Plunger diameter: $\phi 5.80 \pm 0.01$
- Spring diameter: $\phi 5.0^{+0}_{-0.02}$
- Tip radius: R2.56
- Dimensions: 6.0, 2.0, 18.0, 10.00, 36.0

Materials(Plated) (材質與鍍層):

Barrel (針套) : Brass (黃銅) , Au on Ni Plated
 Plunger (針軸) : Brass (黃銅) , Au on Ni Plated
 Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):

Contact Resistance (接觸電阻) : 50mΩ
 Full Stroke (滿沖程) : 10mm
 Spring Force (額定彈力) : 400±10%gf@ load 10mm

標記	夾數	更改文件號	簽字	日期
設計				
校對				
審核				
工藝				

名稱	
SF-PA5.8X36-J/M3	
圖樣標記	質量比例
S A	4:1
共 1 頁	第 1 頁

勝峰探針

說明: 1、所有尺寸的单位为mm
 2、未注图示尺寸公差:
 按GB1804-79 11级精度执行。



SFENG 有限公司 謹啟

Shengyiifurui Electronic Technology Co., Ltd. 專業生產各種電子元件及組件，品質優良，價格公道，歡迎垂詢。
本公司產品符合RoHS標準，無鉛無汞，環保無害。

地址：廣東省深圳市

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

□□□□□□

