




SFENG 1984 (**PH**)



	SF-PH-4
	2.50
B	1.80
c	2.50
d	2.33
e	2.27
F	1.25
	16.0
b	18.0
c	38.0
d	3.0
e	3.0
	10.5
	2.3/2.35
	3.00
	150g
MOQ	100
	7





规格 Spec 型号 Type	SF-PH-1	SF-PH-2	SF-PH-3	SF-PH-4	SF-PH-5	SF-PH-6
A	1.20	1.50	2.00	2.50	3.50	5.00
B	0.75	0.95	1.29	1.80	2.50	3.50
C	1.20	1.50	2.00	2.50	3.50	5.00
D	0.98	1.34	1.83	2.33	3.23	4.55
E	0.98	1.27	1.77	2.27	3.17	4.55
F	0.47	0.56	0.75	1.25	1.62	2.45
a	7.0	10.0	16.0	16.0	16.0	16.0
b	9.5	13.0	16.0	18.0	18.0	19.5
c	20.5	27.0	36.0	38.0	38.0	40.0
d	1.0	2.0	2.0	3.0	3.0	4.0
e	1.0	2.0	2.0	3.0	3.0	1.5
Full travel 行程	3.5	6.0	8.3	10.5	10.0	10.5
Mounting hole size 钻孔尺寸	1.0/1.05	1.3/1.35	1.8/1.85	2.3/2.35	3.2/3.25	4.65/4.7
Recommended min.center 最小间距	1.70	2.00	2.50	3.00	4.20	5.50
Spring force 弹簧压力	100g	150g	150g	150g	200g	250g
Bress,Ni.plated 针轴材质	磷铜	磷铜	磷铜	磷铜	磷铜	磷铜
Connections 接线形式	焊接	焊接	焊接	焊接或插 端子线	焊接或插 端子线	焊接或插 端子线



1. 24
2. OEM
- 3.
- 4.



- 1.PCB ICT FCT
2. 2
3. BGA
- 4.QZ VZ LM
- 5.
- 6.
- 7.30# OK POM



1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection




5. Finished products



6. Packing





□□□□□DHL□UPS□FedEx□TNT□EMS□□□□□□□□

Exwork FOB CNF CIF



Q1. □□□□□□□□

A1:

Q2.□□□□□□□□□□

A2: □□□□□□ QC □□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□ 1 □□□□□□□□

Q3.□□□□□□□□

A3:

Q4. □□□□□□

[illegible]

Q5.

