

□□□□

□□□□	SF1875
□□□	□□5.5×39.0mm
□□	□□□□□□:□□□□□□□□□□ □□□:□□□□□□□□□□ □□□□□: SUS
□□□□□□□	9.0mm
□□□	330±20%gf@load 9.0mm
MOQ	100□
□□□	T/T
□□	□□□□□□□□□□ 5 □ 15 □

□□ □□□□□

(單位) 六角定位針GP8.0×4.2.5 (錐度)

Materials (Plated) (材質與鍍層):
 ① Barrel (針套) : Brass (黃銅) , Ni Plated
 ② Plunger (針軸) : Brass (黃銅) , Ni Plated
 Spring (彈弓) : SUS304 (不銹鋼線) , /

Specifications (技術要求):
 Rated Stroke (額定沖程) : 5.0mm
 Spring Force (額定彈力) : 200gf@ load 5.0mm

				名稱		六角定位針GP8.0×4.2.5 (錐度)		名稱		勝峰探針	
										說明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。	
标记	数量	更改文件号	签字	日期	图样标记	质量	比例				
设计			标准化		S	A	3:1				
校对			审定								
审核			制图	HJQ							
工艺			日期	2018-6-7	共	1	页	第	1	页	

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



Measuring Equipment >



Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test



