□□□□

□□□□	SFENG
□□□□	SF-P11
□□□□□□	□□
□□□	□□
□	SUS□□□□□□□
□□□□□□	150□□□
□□□□	4.0□0.1575 ''□
□□□□□	□3□a□
□□□□□	50□□□□W
□□□	1.90□0.0748 ''□
□□□□□□	1.35□0.532 ''□/ 1.40□0.0551 ''□
MOQ	100 □
□□□□□□	7 □□□□□□□□□□□□□

□□□□□

SF-P11





SP-P11-E

Probe specifications SF-P11(技术规格)

- Recommended minimum center(最小间距):
  1.90mm(.0748 ")
- Mounting hole size(钻孔尺寸):
  压克力：1.35mm(.0532 ")
  电木板、玻璃纤维板：1.40mm(.0551 ")
- Full travel(行程)：4.0(.1575 ")
- Spring force(弹簧压力)：150g
- Materials and finishes(材料及涂饰):
  Plunger:Be Cu,Rh plated
  Barrel:Brass,Gold plated
  Spring:Stainless steel
- Current ration(额定电流)：3A(安培)
- Contact resistance(接触电阻)：50mΩ(毫欧姆)

www.shengfengdz.com

[illegible]

1.[illegible] 24[illegible]

2.[illegible] [illegible]OEM[illegible]

3.[illegible] [illegible]

4.[illegible] [illegible]

[illegible]

PCB[illegible]ICT[illegible]FCT[illegible]

[illegible]2[illegible]&[illegible];[illegible]

BGA[illegible]·[illegible]

□□□□□□□□□□□□QZ□VZ□□□□□LM□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□□□□;

□□□□□&□038;□□□□□□□/□□□□□

□□□□□□□□□□□□□□30□OK□□□□□□□□□□□□POM□□□□□□□□□□□

□□□□

Spring exhausted tester	DC power supply	Current resistance tester
Microscope	Tensile strength tester	Spring tester

□□□□□□□□


胜峰电子