


□□□□

□□□□	SFENG
□□□□	SF-P11
□□□□□□	□□
□□□	□□
□	SUS□□□□□□□□
□□□□□□	150□□□□
□□□□	4.0□0.1575 "□
□□□□□	□3□a□
□□□□□	50□□□□W
□□□	1.90□0.0748 "□
□□□□□□	1.35□0.532 "□/ 1.40□0.0551 "□
MOQ	100 □
□□□□□□	7 □□□□□□□□□□□□

□□□□□

SF-P11



SP-P11-E

Probe specifications SF-P11(技术规格)

- Recommended minimum center(最小间距): 1.90mm(.0748")
- Mounting hole size(钻孔尺寸):
 压克力: 1.35mm(.0532")
 电木板、玻璃纤维板: 1.40mm(.0551")
- Full travel(行程): 4.0(.1575")
- Spring force(弹簧压力): 150g
- Materials and finishes(材料及涂饰):
 Plunger: Be Cu, Rh plated
 Barrel: Brass, Gold plated
 Spring: Stainless steel
- Current ration(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

www.shengfengdz.com



chinapogopinsupplier.com

服务宗旨

1. 提供24小时售后服务
2. 提供OEM定制服务
3. 提供技术支持
4. 提供物流配送

产品

PCB ICT FCT

24小时服务热线: 0755-26000000

BGA

