

□□□□

□□□□	SFENG
ITERM□□	SF-P100
□□□	□□□□
□□□□□□	□□□□□□□□7□□□

SF-P100

SF-P100-E

Probe specifications SF-P100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000 ")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670 ") 电木板、玻璃纤维板: 1.75mm(.0689 ")
- Full travel(行程): 6.40(.2520 ")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰): Plunger: Be Cu, Rh plated; SK4, Rh plated Barrel: Brass, Gold plated Spring: Stainless steel
- Current rating(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

>>>

-A	-U	-H3.0
-B	-V	-LM
-J	-G	-T
-D	-H	-Q
-E	-H2.0	-B3
-U3	-H2.5	-B7

SF-R100

SF-R100

Probe specifications SF-R100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000 ")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670 ") 电木板、玻璃纤维板: 1.75mm(.0689 ")
- Materials and finishes(材料及涂饰): Barrel: Brass, Gold plated
- Connections(接线形式): Crimp: R100-VCR2.5, R100-CR Solder cup: R100-VSC2.5, R100-SC Wire wrap: R100-VW2.5, R100-WW, R100-WW(双环2.5), R100-WW(双环) Terminal: R100-VW2.5(T), R100-WW双环2.5(T), R100-WW双环5.0(T), R100-WW双环(T)

SF-R100-SC

SF-R100-VCR2.5

SF-R100-CR

SF-R100-VW2.5(T)

SF-R100-WW双环2.5(T)

SF-R100-WW双环5.0(T)

SF-R100-WW双环(T)

□□□□

SF-P100-D

SFENG
The China's The World's



www.chinapogopinsupplier.com

SF-P100-B

SFENG
The China's The World's



www.chinapogopinsupplier.com

服務項目

1. 承接各類精密五金零件 24小時服務熱線
2. 承接各類精密五金零件 OEM 加工服務
3. 承接各類精密五金零件 批發零售服務
4. 承接各類精密五金零件 批發零售服務

服務項目

PCB、ICT、FCT、各類精密五金零件、各類精密五金零件

□□□□□□

