



☐☐	SFENG
☐☐ ITerm ☐☐	SF-P100
☐☐	☐☐ ☐☐
☐☐ ☐☐	7 ☐ ☐☐☐☐☐ ☐

SF-P100

SF-P100-E

Probe specifications SF-P100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 亚克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Full travel(行程): 6.40(.2520")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰): Plunger:Be Cu,Rh plated; SK4,Rh plated Barrel:Brass,Gold plated Spring:Stainless steel
- Current ration(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

SF-R100

Probe specifications SF-R100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 亚克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Materials and finishes(材料及涂饰): Barrel:Brass,Gold plated
- Connections(接线形式): Crimp: R100-VCR2.5,R100-CR Solder cup: R100-VSC2.5, R100-SC Wire wrap: R100-VW2.5,R100-WW, R100-WW(双环2.5),R100-WW(双环) Terminal: R100-VW2.5(T),R100-WW双环2.5(T), R100-WW双环5.0(T),R100-WW双环(T)

-19- Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

-20- Noted: Specifications subject to change without notice(注: 规格变动不另行通知)



SF-P100-J

SFENG
The China's The World's



WWW.SF-PROBE.COM

SF-P100-B

SFENG
The China's The World's



www.chinapogopinsupplier.com

關於我們

1. 我們提供 24 小時客戶服務。
2. 我們提供 OEM 服務。
3. 我們提供 24 小時客戶服務，並提供 24 小時客戶服務。
4. 我們提供 24 小時客戶服務，並提供 24 小時客戶服務。

我們提供

PCB, ICT, FCT 測試服務 (SMT);

□□ □ (□□□)□ □□ □□, □□□, □□□ & A□ □□ □ □□ □□ □□□ □□□ □□; A; A; □□ □□ □□□□;

BGA □□□ □□□□□□ □□ □□ □□□;




□ □□ □, QZ □ VZ □□□□ □ LM□□ □□ □;

□□ □□ □□□, □□□ □□□ □□ □□;

□□□ & A; A; A; □□□ / □□□;

□□ □□ □□ □□, □□□ # 30 OK, □□ □□ □□, POM, □ □□ □

□□ □□

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
