9tips PCB □□□ □□□

□□ □□

□□□	9tips PCB □□□ □□□
□□	50mil 75mil 100mil □□ □□□ □□ □
□□ □□	0-50A
□□□ □	□□□
□□ □□	50m Ω

SF-P100



SF-P100-E



Probe specifications SF-P100(技术规格)

- Recommended minimum center(最小间距):
  2.54mm(.1000 ")
- Mounting hole size(钻孔尺寸):
  压克力：1.70mm(.0670 ")
  电木板、玻璃纤维板：1.75mm(.0689 ")
- Full travel(行程)：6.40(.2520 ")
- Spring force(弹簧压力)：200g
- Materials and finishes(材料及涂饰):
  Plunger:Be Cu,Rh plated；SK4,Rh plated
  Barrel:Brass,Gold plated
  Spring:Stainless steel
- Current ration(额定电流)：3A(安培)
- Contact resistance(接触电阻)：50mΩ(毫欧姆)

Noted：Specifications subject to change without notice(注：规格变动不另行通知)

SF-R100



Probe specifications SF-R100(技术规格)

- Recommended minimum center(最小间距):
  2.54mm(.1000 ")
- Mounting hole size(钻孔尺寸):
  压克力：1.70mm(.0670 ")
  电木板、玻璃纤维板：1.75mm(.0689 ")
- Materials and finishes(材料及涂饰):
  Barrel:Brass,Gold plated
- Connectioins(接线形式):
  Crimp：R100-VCR2.5,R100-CR
  Solder cup：R100-VSC2.5，R100-SC
  Wire wrap：R100-VW2.5,R100-WW,
  R100-WW(双环2.5) ,R100-WW(双环)
  Terminal：R100-VW2.5(T),R100-WW双环2.5(T),
  R100-WW双环5.0(T),R100-WW双环(T)

Noted：Specifications subject to change without notice(注：规格变动不另行通知)

1. Raw material warehouse

2. Lathe workshop

3. Assemble workshop

4. Quality inspection

5. Finished products

6. Packing

1. Agilent current testing



2. Quadratic element

3.Load Curve Meter

4.Bond Test

5.Life Fatigue Test

6.Microscope

□□ □ □□

Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.