

胜峰 M3

00

00 00	胜峰 M3
00 0 000	000 : 00, 00 00 00 0 0 ; 00 : 00 00, 0000 000 0000 0 ; 0 : 00000 00 ;
000 0	400g
00 00	3-10 0
00	DHL / TNT / UPS / 000

SF-PA5.8X36-J/M3
www.chinapogopinsupplier.com

Materials (Plated) (材質與鍍層):

Barrel (針套) : Brass (黃銅) , Au on Ni Plated

Plunger (針軸) : Brass (黃銅) , Au on Ni Plated

Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):

Contact Resistance (接觸電阻) : 50mΩ

Full Stroke (滿沖程) : 10mm

Spring Force (觸定彈力) : 400±10%gf @ load 10mm


				名稱		胜峰探针	
				SF-PA5.8X36-J/M3			
标记	页数	更改文件号	签字	日期	说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。		
设计			标准化				
校对			审定				
审核			制图	徐松孟			
工艺			日期	2016.10.07			
					图样标记	质量比例	
					S A	4:1	
					共 1 页	第 1 页	




SFENG 有限公司

Shengyifurui 有限公司 Co., 有限公司, 有限公司 & 有限公司. 有限公司
RoH 有限公司.


有限公司



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope



Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.

