

□□ □□

□□ □□	SF3147
□□□□□	≥10mm
□□□ □	200gf@□□5.0mm
□□□	□□, □□□□
□	□□, □□□□
□	SUS304
□□□□ □□	OEM & ODM
MOQ	100PCS
□□□	Plastic bag, carton box
□□	□□ □ 100% T/T
□□ □□	□□□□ □□ □ 5~10□

□□ □□

温度探针

尼龙6含30%玻璃纤维，  
加阻燃

Materials(Plated) (材質與鍍層) :

- Barrel(針套) : Brass(黃銅) , Ni Plated
- Plunger(針軸) : Brass(黃銅) , Ni Plated
- Spring(彈弓) : SUS304(不鏽鋼) , /

Specifications (技術要求) :

- Full Stroke(滿沖程) : >10.0mm
- Spring Force(額定彈力) : 200gf@ load 5.0mm

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



## Measuring Equipment >



### Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test





## □□ □□

1. PCB, ICT, FCT □□ □□ □□ □□ □□ (□□);
2. □□, □□ □□, □□□, □□□ □ □□□□□ □□ □ □□ □□ □□ □□□ □□ □□□ □□ □□□;
3. BGA □ □□□ □□□□ □□ □□ □□ □□;
4. □□□□ □□ □□ □, □□ □, QZ □ VZ □□□□ □□ LM □;
5. □□□ □□□, □□□ □□□, □□□□□ □□;
6. □□□ □ □□□/□□;
7. □□ □□ □□ □□, □□ □□ □□, POM □ □.

□□□ □□□□ □□ □□ □□□□ □□ □□□□. □□□ □□□ □□ □□□ □□ □□□ □□□□ □□ □□□ □□ □□□.

## □□□ □□□

1. □□□ □□□ □□□ □□□□ 24□□ □□□ □□□ □□ □ □□□□.
2. □□□ □□□□ □□□□ OEM□ □□□□□.
3. □□□□ □ □□ □□□□ □□□ □□□□ □□□ □□ □□□□.
4. □□□ □□□□ □□□□ □□□ □□ □□□□ □□□ □ □□□□.