

00 00

00	SFENG
00 00	SF-P100
000	00 00 Becu, 0 00 00 00
0	00, 0 00 00 00
0	SK4 00 000
0 00	200g
00 00	6.4mm
00 00	3A
00 00	50MΩ
00	2.54MM
00 00 00	00 1.7mm
MOQ	(100) 0
00 00	7 00000 0 000

00 00









000 000

1. Reply 24 00 00 withn 00
2. Customized 0000 0000, OEM 00
3. Delivery 000 0000 0 00 0000 000 0
4. provide 000 0000 00 00 00 00

00 00

- 000 0 0 PCB, ICT, FCT 000000 (00)
- 00 0 (000) 000 (usually temporary) 000 00000
- 0 , 00 000, 000 & A 00000 00 00 00;
- interconnectApplications;
- 00 00 probef orBGA & A, semiconudtion 000;
- 00 0 000, coatingpin, LM 0 withQZ & A; VZseries;
- 00 00 000, 000 000, 00 00 ...
- 000 & A, 00 / 00;
- 00 00 00 compents, 30 # OKwire, 00 00 00, POM, Ironhinge 0

□□ □□

Spring exhausted tester	DC power supply	Current resistance tester
 A tall, white, cabinet-style machine with a glass door on the upper half and a control panel on the right side.	 A white, rectangular benchtop power supply. The front panel features a red power switch, a red output terminal, a black output terminal, and a blue output terminal. The brand name 'YoRi' and 'ADJUSTABLE DC POWER SUPPLY' are visible on the top.	 A white benchtop device with a large green digital display showing '8888'. It has a 'BLIND TEST' warning symbol and a 'VDC' label. The brand name 'YOYI' is visible at the bottom.
Microscope	Tensile strength tester	Spring tester
 A white and black compound microscope with a large objective lens and a camera attachment on top.	 A blue and white mechanical testing machine with a vertical column and a sample holder.	 A white mechanical testing machine with a digital display and a control panel, used for testing springs.

□□ □□

