

□□ □□

□□ □□	SF3081
□□ □□□□	5.0mm
□□□□	8000g
□□□ □□□/□□	□□/□
□□ □□□/□□1	POM
□	SUS304
□□ □□□/□□2	□□ □□□
□□□	150□□□
□□	<0.5mΩ
□□	ΔT<20°C
□□□ □□	OEM& ODM
MOQ	100PCS
□□□	Plastic bag, carton box
□□	□□ □ 100% T/T
□□ □□	□□□ □□ □ 5-10□

□□ □□

SF-18.0*76.0

Materials(Plated) (材質與鍍層) :
 Barrel(針套) : POM(賽鋼) , /
 Plunger(電壓針軸) : BeCu(鈹銅) , Au on Ni Plated
 Plunger(電流針軸) : Cu(探針專用銅) , Au on Ni Plated
 Spring(彈弓) : Spring Wire(彈簧鋼線) , Ni Plate
 Insulator(絕緣體) : PEEK or PTFE , /

Specifications (技術要求) :
 Current Rating(額定電流) : ??A
 Contact Resistance(接觸電阻) : ??mΩ

名稱	移動距離(mm)	1/2壓縮	全壓縮
電流針	12	11kgf	15.5kgf
電壓針	3	-	1200gf

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection




5. Finished products



6. Packing



Measuring Equipment >



Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test



