□□□

□□	SFENG
□□	□□□ □□□ SF-KP2.96 * 54 □□ □
□□□	□□□
□□	□□
□	□□□□□
□□□ □	□□□
□□ □□	5.0 mm
□□ □□	□□
□□ □□	□□
□□	□□
□□ □□	□□
MOQ	100
□□ □□	□□ □□ □ 7 □

□□ □□□

SFENG
The China's The World's

□□□ □□□ □□□ □□



材质与电镀；
①针　头，　磷铜镀金；
②套　管，　黄铜镀镍；
③绝缘套，　PEEK；
④尾　针，　磷铜镀金；
⑤绝缘套，白色POM

技术要求；
满行程：5.0mm
满行程弹力：450g±90g
开关距离：1.5mm
开关弹力：120g±25g

标记	处数	更改文件号	签　字	日　期
设　计		标准化		
校　对		审　定		
审　核		制　图	HJQ	
工　艺		日　期	2018-11-8	

名　称：
SF-开关针新PEEK 2.96X54带塑料头

图样标记	视图	质量	比例
S A			1:1
共 1 页	第 1 页		

胜峰科技

说明：
1.所有尺寸单位为mm
2.未注图示尺寸公差:按GB1804-79 11级精度执行

图纸编号：

□□□ □□□

1. □□ □□.

2. □□□ □□ □□□□□.

3. □□ □□ □□ □ □□ □□.

4. □□□□ □□ □□.

□□ □□

PCB, ICT, FCT □□□□ □□□□□ □ (□□);

□□, □□□□, □□□, □□□ □ □□□□□□ 2 □□ □□ □□ □□ □□□ □□□ □□□□□□ □□□ □ (□□□); □□ □□ □□□□□□;

BGA □ □□□ □□□ □□ □□ □□□;

□□ □ □□□ □□, □□□ □□, LM □ QZ □ VZ □□□;

□□□ □□□, □□□ □□□, □□□□ □□;

□□□ □□□; □□ / □□;

□□ □□ □□ □□, 30 # OK □□, □□ □□, POM, □ □□ □

□□ □□

1. Raw material warehouse

2. Lathe workshop

3. Assemble workshop

4. Quality inspection

5. Finished products

6. Packing

□□ □□

1. Agilent current testing



2. Quadratic element

3.Load Curve Meter

4.Bond Test

5.Life Fatigue Test

6.Microscope

□□ □ □□

Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.