

□□ □□


□□	SFENG
□□ □□	125mil □□□ □□ □□□ □□□
□□□	SF-PA125
□□□	Cu, □ / □□ □□
□	□□, □□□
□	□□□□□
□□□ □	2N (7.2oz)
MOQ	100 □



Probe specifications SF-P156(技术规格)

- Recommended minimum center(最小间距): 4.75mm(.1870")
- Mounting hole size(钻孔尺寸): 压克力: 2.75mm(.1083")
电木板、玻璃纤维板: 2.80mm(.1102")
- Full travel(行程): 6.30(.2480")
- Spring force(弹簧压力): 250g
- Materials and finishes(材料及涂饰):
Plunger: Be Cu, Rh plated;
Barrel: Brass, Gold plated
Spring: Stainless steel
- Current ration(额定电流): 5A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)
- Connections(接线形式):
Crimp: R156-VCR, R156-CR
Solder cup: R156-VSC, R156-SC

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)



SFENG
The China's The World's





公司 优势

1. 拥有 24 小时 客户 服务热线。
2. 拥有 完善 的质量 管理体系 和 先进的 OEM 生产能力。
3. 拥有 丰富 的 行业 经验 和 专业的 技术 团队。
4. 拥有 广泛 的 客户 基础和 良好的 市场 口碑。

产品 应用

PCB, ICT, FCT 等行业 的 各种 精密 加工 (钻孔);

五金, 机械, 模具, 航空航天 等 领域的 各种 精密 加工 (钻孔);

BGA 等 各种 精密 加工 的 专用 钻头;

各种 规格 的 钻头, 丝锥, QZ 及 VZ 系列 的 LM 钻头;

000 000, 000 000, 00000 00;
 000 0 0000 / 00;
 00 00 00 00, 30 # OK 000, 00 00 00, POM, 0 00 0
 00



00 00



1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection




5. Finished products




6. Packing


00 00



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope

□□□ & □□

Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.



**FAST
DELIVERY**