

□□ □□

□□	SF-PPA 5.5X24
□□□	□□
□□	□□
□	□□□□□ □□
□□□ □	300g±20%
MOQ	500□
□□□□	7 □

□□ □□

由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

NOTE

- Material  
Plunger: Brass C3604  
Barrel: Brass C3604  
Spring: SUS304  
Housing:
- Plating  
Plunger: Au 2u" over 50~120u" Ni  
Barrel: Au 2u" over 50~120u" Ni  
Spring:
- Electrical  
Rated current & voltage: DC 12V; 1.0A Max.
- Mechanical  
Spring force: **300g±20%** at normal working height  
Durability: 10,000 cycles(minimum)
- To ensure the best usage, please operate it based on the working height  
Based on the engineering drawings, shall not exceed the maximum allowed compression
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- RoHS And REACH compliant product.

由 Autodesk 教育版产品制作

截面内部示意图

SF-PPA5.5X24

第三角法		品名	PO80pin	日期	2022/04/26
未注公差参照标准	0.02	规格		设计	ZHU XU
0 - ±0.1	0.03	材质		审核	
0.0 - ±0.05	0.02	客户料号		确认	
0.00 - ±0.02	0.04	表面处理	镀金	单位	mm
0.000 - -	0.02	图号		比例	1:1 版本 REV:A
请见实物图纸					

□□

